



# SU-6500

LTE-M (Cat-M1)/NB-IoT

Compact and ultra-rugged battery-powered GPS asset tracker featuring 10+ years battery life



84 x 63 x 24 mm (3.31 x 2.48 x 0.94 in)

## 'Deploy Once' Battery Life

Over 10+ years battery life at once-daily location updates

## User-Replaceable Batteries

Uses off-the-shelf 3 x AAA batteries

## Adaptive Tracking

Periodic or optional movement-based tracking - tracks assets throughout the day and/or when movement occurs, entering sleep mode when inactive to conserve power and data usage

## Battery Life Alerts

"Battery Low" and "Battery Critical" alerts

## Ultra-Rugged

Ultra-rugged and weatherproof IP68, IK06 Housing

# Connectivity

<b>LTE-M / NB-IoT</b>	Nordic nRF9160 Modem operates on all major global LTE-M and NB-IoT bands. Supported LTE bands:
(supports roaming between networks - roaming SIM required)	LTE-M (Cat-M1): B1, B2, B3, B4, B5, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B66 NB-IoT (Cat-NB1/NB2): B1, B2, B3, B4, B5, B8, B12, B13, B17, B19, B20, B25, B26, B28, B66
<b>SIM Size &amp; Access</b>	Internal Nano 4FF SIM

# Location

<b>GNSS</b>	Sony CXD5605
<b>Constellation</b>	Concurrent GPS, GLONASS, Galileo, QZSS
<b>Tracking Sensitivity</b>	-147 dBm cold start / -161 dBm hot start
<b>*Location Accuracy</b>	~1m 2D RMS, GPS, -130dBm
<b>GNSS Assistance</b>	GNSS almanac and ephemeris data for greater sensitivity and position accuracy
<b>Low Noise Amplifier</b>	GPS signals are filtered and boosted by a SAW filter and low-noise amplifier (LNA) allowing operation where other units fail
<b>Cell Tower Location</b>	Cell tower location fallback for positioning when GPS can't get a fix

\* Positioning accuracy specifications are provided by the GNSS supplier and reflect ideal conditions. Device configuration, installation, environmental conditions, augmentation services, and many other factors may lead to variations in positioning accuracy.

# Power

<b>Input Voltage</b>	3-5.5V
<b>Sleep Current</b>	<10uA* *Average current in lowest power configuration

# Batteries

<b>User-Replaceable Batteries</b>	3 x AAA. <i>Batteries not included.</i>
<b>Supported Battery Types</b>	*Lithium (LiFeS2) - recommended for best performance  *Please dispose of Lithium batteries in a safe and responsible manner
<b>*Battery Life Estimates</b>	Once Daily location updates - 10 years **Movement-Based location updates - 2 years Hourly location updates - 1.5 years

\* Battery life estimates are influenced by several factors including temperature, installation and orientation of the device, the frequency of location updates, network coverage, sensor integrations, peripherals, accelerometer settings, and more.

\*\* Movement-based estimates are based on 2 hours of movement, occurring 5 days a week, with default tracking parameters (location updates every 3 minutes and uploads every 30 minutes). Devices can be configured to provide more frequent location updates when the asset is in motion.

# Mechanics / Design

Dimensions	Standard - 84 x 63 x 24 mm (3.31 x 2.48 x 0.94") Livestock Collar - 109 x 60 x 30 (4.29 x 2.36 x 1.18")
Housing	Non-branded housing for optional white-labeling
IP/IK Rating	Ultra-rugged and waterproof IP68 and IK06-rated housing ensures the SU-6500 can withstand impact, fine dust, and brief submersion
Installation	Compact and concealable. Multiple installation options for covertly and easily securing the device to assets with screws, bolts, cable ties, rivets, and more. Collar housing available for securing device to livestock. Stainless steel screws supplied.
Operating Temperature	-30°C to +60°C
Cellular Antenna	Internal
GPS Antenna	Internal
3-Axis Accelerometer	3-Axis Accelerometer to detect movement, high G-force events
Diagnostic LED	Diagnostic LED indicates operation status
Flash Memory	Store weeks of records if device is out of cellular coverage. Storage capacity for over 2 weeks of 2-minute logging.
Onboard Speed and Heading	Current speed and heading is reported with each position update
Onboard Temperature	The device reports internal temperature which provides an indication of ambient temperature but may not always be precise

# Smarts

Auto-APN	Auto-APN allows the device to analyze the SIM card and select the correct APN details from a list that is pre-loaded in the device's firmware
Battery Life Monitoring	"Battery Low" and "Battery Critical" alert levels
Geofence Alerts	The server can use device location to create geofences and alerts if an asset enters or leaves designated locations
Onboard Geofencing	Geofences can be downloaded directly to the device for enhanced location-based actions and alerts. Maximum of 100 Geofences with up to 100 points per geofence.
Impact Detection	Configure impact-detection alerts when G-forces are exceeded by a user-defined threshold
Intelligent Power Management	Early registration abort and location scan throttling options
Periodic or Movement-Based Tracking	Configure parameters to send updates based on set time intervals or when movement occurs. Adaptive tracking technology detects when the device is on the move and increases the update rate, providing detail when you need it while conserving battery when stationary.
Preventative Maintenance	Set reminders based on distance traveled and run hours to reduce maintenance and repair costs
Run Hour Monitoring	Capture run hours based on movement to understand and optimize asset utilization
Sleep Mode	Stationary devices enter sleep mode until movement occurs to conserve battery life and optimize data usage
Theft Recovery	Switch to Recovery Mode in the case of theft or loss to activate real-time tracking for asset retrieval
Tip Detection & Rotation Counting	Axis angle reporting, tip detection and rotation counting

# Device Management

---

Flexible Configuration	Configure device parameters such as position update rate, movement and accelerometer settings, and more to fit any tracking application
Device Management Platform	Manage, monitor, configure, debug, update, and restart devices remotely from our cloud-based device management system
Configuration App	Configurable with DMLink Provisioning tool

---

# Integration

---

Third-Party Integration	TCP Direct or HTTPS Webhook
-------------------------	-----------------------------

---

# Security

---

Data Security	Military-level AES-256 Encryption from device to Device Management Platform to protect the integrity and confidentiality of telematics data. Data forwarded to third-party systems is sent via HTTPS for end-to-end security.
---------------	---

---

# Warranty

---

Manufacturer's Warranty	Two-year manufacturer's warranty. <a href="#">Exclusions apply.</a>
-------------------------	---

---

# Certifications

---

Please check our knowledge base for [regulatory and network certifications](#)

---